

2500 AC DUAL HEAD PUMP

The Helios 2500AC Dual Head Pump showcases a wide range of user-friendly characteristics and highly efficient repair capabilities. With its maximum pressure rating of 2500PSI, this pump delivers flexible injection rates, spanning from 1/2 pint to 40 Gallons per day per fluid head.

WORK. SIMPLY.

KEY FEATURES

- 6 Position Variable Displacement Follower
~ Reduces Volume by 12% for Each Position

- 316 Stainless Steel "Fast Pack" Fluid Head
~ Reduce Packing Replacement Time by 50%

- Check Valves Include Tungsten Carbide Balls & Teflon Seals

- Heavy Duty Sealed Ball Bearing Cam

- Continuous 5/8" Keyed Driveshaft w/ Front Support Bearing

- O-Ring Sealed Lid

- Remote Automation Control & Tank Level Monitoring


- RS 485 Modbus RTU

- Tank Level Input

- Temperature Control



2500 Series Single Head Injection Rates



MOTOR: 1/20HP-30RPM 115VAC

FLUID ENDS: 316 Stainless Steel, Teflon Seat SS Check Valve

PLUNGERS: 1/4", 3/8" or 1/2" 316 Stainless Steel

PACKING TYPES: Buna, Viton, HNBR, & ETP

CONTROLLER: Helios Digital Tru Timer: Includes Temperature Control, Modbus, and Tank Level Input

UPGRADES: Ceramic Coated Plungers, & Hastelloy, PPS Plastic, Fluid Head Assemblies Available

WEIGHT: 34.5 lbs

DIMENSIONS: 17 x 21.5 x 13.5 in

www.heliospumps.com Visit us online to find a Helios location near you.