

5000 AC/DC VARIABLE SPEED TRIPLEX HEAD PUMP

The Helios 5000 AC/DC Variable Speed Triplex Head Pump showcases a wide range of user-friendly characteristics and highly efficient repair capabilities. With its maximum pressure rating of 5000PSI, this pump delivers flexible injection rates, spanning from 1 pint to 363 gallons per day per fluid head.

WORK. SIMPLY.

KEY FEATURES

- 6 Position Variable Displacement Follower
~ Reduces Volume by 12% for Each Position

- 316 Stainless Steel "Fast Pack" Fluid Head
~ Reduce Packing Replacement Time by 50%

- Check Valves Include Tungsten Carbide Balls & Teflon Seals

- Heavy Duty Sealed Ball Bearing Cam

- Continuous 5/8" Keyed Driveshaft w/ Front Support Bearing

- O-Ring Sealed Lid

- Remote Automation Control & Tank Level Monitoring*

- RS 485 Modbus RTU*


- Tank Level Input*

- Temperature Control*

*Optional Equipment Required



5000 Series Single Head Injection Rates



MOTOR: 1/6HP - 60RPM 115VAC

FLUID ENDS: 316 Stainless Steel, Teflon Seat SS Check Valve

PLUNGERS: 1/4", 3/8", 1/2", 3/4", or 1" 316 Stainless Steel

PACKING TYPES: Buna, Viton, HNBR, & ETP

CONTROLLER: Variable Speed Knob

UPGRADES: Ceramic Coated Plungers, & Hastelloy, PPS Plastic, 3/4" & 1" Fluid Head Assemblies Available

WEIGHT: 49.75 lbs

DIMENSIONS: 20 x 21 x 10.25 in

www.heliospumps.com Visit us online to find a Helios location near you.